[API Name] Documentation

Version [v1] · Last updated [date]

Overview

[What the API does and who it is for.]

Base URL [https://api.example.com/v1]

Format JSON

Support [email or link]

Authentication

[Describe how to get and use credentials, e.g. send your API key in the Authorization header.]

```
Authorization: Bearer [YOUR_API_KEY]
```

Endpoint: [List items]

```
GET /[items]
```

[Short description of what the endpoint returns.]

Query parameters

Name	Type	Required	Description
limit	integer	No	[Number of results to return (default 20, max 100)]
cursor	string	No	[Cursor for the next page of results]

Example request

```
curl https://api.example.com/v1/[items]?limit=2 \
  -H "Authorization: Bearer [YOUR_API_KEY]"
```

Example response (200 OK)

```
{
  "data": [
    { "id": "itm_123", "name": "[Example]", "created_at": "2027-03-01T12:00:00Z" }
  ],
  "next_cursor": "[abc123]"
}
```

Endpoint: [Create item]

```
POST /[items]
```

Body parameters

Name	Type	Required	Description

Name	Type	Required	Description
name	string	Yes	[Description]

Errors

Status code	Meaning	What to do
400	Bad request	Check required fields and formats
401	Unauthorized	Check your API key
403	Forbidden	Your key lacks permission for this action
404	Not found	Check the resource ID or URL
429	Too many requests	Slow down; retry after the time in the Retry-After header
500	Server error	Retry later; contact support if it continues

Rate limits

[e.g. 100 requests per minute per API key. Limits are returned in X-RateLimit headers.]

Changelog

Date	Version	Change